Portable Incubator LX901PI

Email: info@labdex.com **website:** www.labdex.com

Description

Portable Incubator LX901PI is designed with a PID controller system with an LED display for setting and visualization of temperatures and timer. The inner chamber is made up of mirror stainless steel and the outer shell is made up of cold rolling steel electrostatic spraying exterior. Built-in safety alarm functions such as over-temperature protection function, over-temperature alarm, and sensor fault alarm.

Specifications

Volume	12.8 L
Shelf number	2
Load per rack	5 kg
Shelf Space	35 mm
Temp. range	RT+5-65℃
Temp. resolution ratio	0.1℃
Temp. motion	±0.5℃
Temp. uniformity	±1.5℃
Temp. control mode	PID Intelligent
Temp. setting mode	Touch button setting
Temp. display mode	Measuring temperature: LED upper row; Setting temperature: the lower row
Timer	0-9999min (with timing wait function)
Operation function	Fixed temperature operation, Timing function, Auto stop

Sensor	PT100
Safety device	Over temperature sound-light alarm
Structure Inner chamber	Mirror stainless steel
Outer shell	Cold rolling steel electrostatic spraying exterior
Insulation layer	Polyurethane
Heater	Heating wire
Power rating	0.12 kW
Power supply	AC220V/0.36A
Inner chamber dimension (W x L x H)	230 x 200 x 280 mm
Exterior dimension (W x L x H)	310 x 280 x 380 mm
Net weight	12 kg
Packing dimension (W x L x H)	350 x 310 x 460 mm
Gross weight	14 kg

Features

- LED display for viewing the work status
- Internal natural air convection with a four-sided heating method
- Equipped with high-quality glass window and LED lights on the door, easy to observe the sample inside, especially under dark conditions
- It is a portable design, making it easy to move

Applications

- Used in food processing, agriculture, biochemistry, biology, and medicine industry for bacterium and microorganism culturing experiments, etc.

71-75 Shelton Street Covent Garden, London WC2H 9JQ UK.

Email: info@labdex.com | Website: www.labdex.com